

FLUID SPECIFICATIONS (U.S. & Mexico) 2010 MY							
Vehicle Model		Engine Type	Engine Oil (Drain & Refill w/Filter Change)	Coolant <i>Toyota Super Long Life Coolant (SLLC)</i>	Manual Transmission	Automatic Transmission	Transfer Case
			2010			Drain & Refill	
4Runner	1GR-FE	0W-20 6.6qts.	11.1qts. SLLC		ATF WS*: A750E(F): 1.8qts.	API GL-5 75W-90 VF4A: 1.1 qts. VF4BM: 1.5 qts.	LT API GL-5 75W-85 Front: Std. 1.43-1.53 qts., w/A.D.D. 1.59-1.69 qts. Rear: Std. 2.8-2.91 qts., w/Diff. Lock 2.75-2.85 qts.
	2TR-FE	0W-20 6.1qts.	8.6qts.		ATF WS*		
Avalon	2GR-FE	5W-30 6.4qt.	8.8qt. SLLC		ATF WS*: U660E: 3.0qts.		
Avanza	3SZ-VE	10W-40 3.0qts	SLLC M/T: 7.3qts; A/T: 7.2qt.	API GL-4 75W-90 1.3qt.	Dexron®III 1.6qt.		API GL-5 80W-90, 85W-90, or 90 1.53-1.85qts.
	K3-VE	10W-40 3.0qts	SLLC Narrow Radiator: 6.3qt. Full Wide Radiator: 7.1qt.				
Camry	2AR-FE	0W-20 4.4qt.	7.5qt. SLLC	SAE 75W EB62: 2.5qt.	ATF WS* Drain & Refill: 2.9qts.		
	2GR-FE	5W-30 6.1qt.	9.5qt. SLLC		ATF WS* U660E: 3.0qts.		
Camry HV	2AZ-FXE	0W-20 ⁹ 5W-20 4.5qt.	Gas Engine: 6.6qt. SLLC Inverter: 3.1qt. SLLC		ATF WS P311: 4.3qt.		
Corolla	2ZR-FE	0W-20 ⁹ 5W-20 4.4qt.	5.8qt. SLLC	API GL-4 or GL-5 75W-90 5-SPD: 2.0qt.	ATF WS*: U341E 2.6qt.		
	2AZ-FE	0W-20 ⁹ 5W-20 4.0qt.	6.0qt. SLLC	API GL-4 75W C59: 5-SPD: 2.6qt.	ATF WS*: U250E 3.7qt.		
FJ Cruiser	1GR-FE	0W-20 6.4qts.	SLLC Manual Trans: 9.9qt. Automatic Trans: 10.4qt.	API GL-4 75W E351: 5-SPD: 1.9qt.	ATF WS*: A750E(F): 1.8qts.	API GL-5 75W-90 VF4B: 1.5qt. VF2A: 1.1qt.	LT API GL-5 75W-85 Front: w/ A.D.D. 1.64 qts. w/o A.D.D. 1.48 qts. Rear: w/dif. Lock: 2.6qts. w/o dif. Lock: 2.64qts.
Hiace	2TR-FE	5W-30 10W-30 7.4qts	SLLC w/ rear heater: 15.8qt. SLLC w/o rear heater: 13.7qt. SLLC	API GL-4 or GL-5 75W-90 RA61F: 1.9qt.	ATF T-IV A340E & A343E: 2.9qt.		API GL-5 90 ³ ; API GL-5 SAE 80W or 80W-90 ⁴ Standard Body: 3.28qt. Wide Body: 3.43qt.
Highlander	2GR-FE	5W-20 ⁶ 5W-30 ⁶ 6.4qts	SLLC w/rear A/C: 11.6qt. ⁶ (12.4qt. ⁵) w/o rear A/C: 9.3qt. ⁶ (10.1qt. ⁵)		ATF WS: 3.7qt.	API GL-5 90 1.0 qt.	API GL-5 90 1.0 qt.
	1AR-FE	0W-20 ⁹ 5W-30 4.2qts.	SLLC w/rear A/C: 9.6qt. ⁶ (10.4qt. ⁵) w/o rear A/C: 7.3qt. ⁶ (8.0qt. ⁵)		ATF WS* U760E: 2.9qts.		
Highlander HV	3MZ-FE	0W-20 ⁹ 5W-20 5.0qts.	Gas Engine: SLLC w/rear A/C: 13.5qt. w/o rear A/C: 11.2qt. Inverter: 3.6qt.		Front: ATF WS 4.4qt. AWD Rear: ATF WS 1.9qt.		
Hilux	2TR-FE	5W-30 10W-30 7.4qts	SLLC w/heater: 8.2qt. w/o heater: 7.4qt.				LSD API GL-5 SAE 90 ³ ; API GL-5 SAE 80 or 80W-90 ⁴ w/LSD: 3.6qt. API GL-5 SAE 90 ³ ; API GL-5 SAE 80 or 80W-90 ⁴ w/o LSD: 2.6qt.
Land Cruiser	3UR-FE	0W-20 ⁹ 5W-20 7.4qts.	17.6qt. SLLC		ATF WS*: AB60F: 2.2qts.	API GL-5 75W-90 JF2A: 1.53qt.	LT 75W-85 GL-5 Front: 1.95qt. Rear: 4.25qt.

1-Abv 40°F

2-Blw 40°F

3-Abv 0°F

4-Blw 0°F

*Refer to ATF adjust in the RM

5-w/twg pkg

6-w/o twg pkg

7-2WD exc PreRunner

8-4WD and PreRunner

9-Best choice for fuel economy and cold starting

FLUID SPECIFICATIONS (U.S. & Mexico) 2010 MY							
Toyota				Scion			
Vehicle Model	Engine Type	Engine Oil (Drain & Refill w /Filter Change)	Coolant <i>Toyota Super Long Life Coolant (SLLC)</i>	Manual Transmission	Automatic Transmission	Transfer Case	Front and Rear Differential
		2010			Drain & Refill		
Matrix	2ZR-FE	0W-20 ⁹ 5W-20 4.4qt.	5.5qt. SLLC	API GL-4 or GL-5 75W-90 C60: 2.4qt.	ATF WS: U341E Drain & Refill: 2.6qt.		
	2AZ-FE	0W-20 ⁹ 5W-20 4.0qt.	6.0qt. SLLC	API GL-4 75W C59: 2.0qt.	ATF WS: U250E & U140F Drain & Refill: 3.7qt.	API GL-5 SAE 90 ³ ; API GL-5 SAE 85 or 85W-90 ⁴ MF1A: 0.8qt.	API GL-5 SAE 90 ³ ; API GL-5 SAE 85W or 85W-90 ⁴ 4WD Rear: 0.53qt.
Prius	2ZR-FXE	0W-20 4.4 qt.	SLLC Engine w/Exh. Recirc.: 7.7qt. Engine w/o Exh. Recirc.: 6.8qt. Invertor: 2.2qt.		ATF WS: 3.5qt.		
RAV4	2AR-FE	0W-20 ⁹ 5W-20 4.6qts.	7.2qt. SLLC		ATF WS* Drain & Refill: 2.9qts.	API GL-5 SAE 90 ³ ; API GL-5 SAE 85 or 85W-90 ⁴ GF1A: 0.48qt.	API GL-5 SAE 85W-90 4WD Rear: 0.48-0.55qts.
	2GR-FE	5W-30 6.4qts.	SLLC 9.4qts. Std 9.8qts. Towing		ATF WS* U660E: 3.0qts.		
Sequoia	1UR-FE	0W-20 7.4qts.	SLLC 14.5qt. ⁶ (15.6qt. ⁵)		ATF WS*: A750E(F): 1.8qts.	API GL-5 SAE 75W-90 1.43qts.	LT 75W-85 GL-5 Front: 2.17qts Rear: 1.64qts.
	3UR-FE & 3UR-FBE	0W-20 ⁹ 5W-20 7.4qts.	SLLC 14.5qt. ⁶ (15.4qt. ⁵)		ATF WS*: AB60E(F): 2.2qts.		
Sienna	2GR-FE	5W-30 6.4qts.	12.0qt. SLLC		ATF WS*: 3.7qts.	API GL-5 SAE 90 1.0qts.	API GL-5 SAE 90 1.0qts.
Tacoma	2TR-FE	0W-20 ⁹ 5W-20 6.1qts.	SLLC M/T: 9.2qts; A/T: 9.1qt.	API GL-4 or GL-5 75W-90 R155 (2WD): 2.7qt. R155F (4WD): 2.3qt.	ATF T-IV A340E: 2.1qt.	API GL-5 SAE 75W-90 1.1qts.	API GL-4 or GL-5 75W-85 Front: 1.59qts. Rear 2WD: 3.66qts. Rear 4WD and PreRunner: 3.12qts.
	1GR-FE	5W-30 2WD: 4.8qts. 4WD and PreRunner: 5.5qts.	SLLC M/T: 10.3qts; A/T: 10.1qt.	API GL-4 or GL-5 75W-90 1.9qts.	ATF WS*: A750E(F): 1.8qts.		
Tundra	1GR-FE	5W-30 5.5qt.	SLLC 10.1qt. SLLC		ATF WS*: A750E: 1.8qts.		LT 75W-85 GL-5 Front: 2.2qts Rear: Regular Cab: 4.23-4.33qts. All others: 4.81-4.91qts.
	1UR-FE	0W-20 7.4 qt.	SLLC 12.8qt. ⁶ (13.9qt. ⁵)		ATF WS*: A750E(F): 1.8qts.	API GL-4 or GL-5 75W-90 JF1A: 1.2qt.	
	3UR-FE & 3UR-FBE	0W-20 ⁹ 5W-20 7.4qt.	SLLC 12.8qt. ⁶ (13.7qt. ⁵)		ATF WS*: AB60E(F): 2.2qts.	API GL-4 or GL-5 75W-90 JF1A: 1.2qt.	LT 75W-85 GL-5 Front: 2.2qts Rear: Regular Cab: Std. Bed: 3.7qt. Long Bed: 3.8qt. Double Cab: Std Bed: 3.8qt. Long Bed: 4.0qt. Crew Max: 2WD: 4.0qt. 4WD: 3.8qt.
Venza	1AR-FE	0W-20 ⁹ 5W-20 4.7qts.	7.9 qt. SLLC		ATF WS* U760E: 2.9qts.	API GL-5 SAE 85W-90 MF1A: 0.8qt.	API GL-5 SAE 90 ³ ; API GL-5 SAE 80 or 80W-90 ⁴ Rear: 0.52qt.
	2GR-FE	5W-30 6.4qts.	SLLC 10.4qt. ⁶ (10.6qt. ⁵)		ATF WS* U660E: 3.0qts.		
Yaris	1NZ-FE	5W-30 3.9qts.	SLLC Manual Trans: 5.1qt. Automatic Trans: 5.0qt.	API GL-4 or GL-5 75W-90 C50: 2.0qt.	ATF WS U340E: 2.6qt.		
Scion tC	2AZ-FE	0W-20 ⁹ 5W-20 4.0qt.	SLLC M/T 7.2qt.; A/T 7.1qt.	API GL-4 or GL-5 75W-90 C50: 2.0qt.	ATF WS U241E: 3.7qt.		

1-Abv 40°F

2-Blw 40°F

3-Abv 0°F

4-Blw 0°F

*Refer to ATF adjust in the RM

5-w/twg pkg

6-w/o twg pkg

7-2WD exc PreRunner

8-4WD and PreRunner

9-Best choice for fuel economy and cold starting

FLUID SPECIFICATIONS (U.S. & Mexico) 2010 MY							
				 Toyota		 Scion	
Vehicle Model	Engine Type	Engine Oil (Drain & Refill w/Filter Change)	Coolant <i>Toyota Super Long Life Coolant (SLLC)</i>	Manual Transmission	Automatic Transmission	Transfer Case	Front and Rear Differential
		2010			Drain & Refill		
Scion xB	2AZ-FE	0W-20 ⁹ 5W-20 4.5qt.	SLLC M/T 6.3qt.; A/T 6.2qt.	API GL-4 or GL-5 75W-90 E351: 2.6qt.	ATF WS U241E: 3.7qt.		
Scion xD	2ZR-FE	0W-20 4.4qt.	SLLC M/T 5.3qt.; A/T 5.2qt.	LV API GL-4 75W C50: 2.0qt.	ATF WS U341E: 2.6qt.		

1-Abv 40°F
2-Blw 40°F
3-Abv 0°F
4-Blw 0°F

*Refer to ATF adjust in the RM

5-w/twg pkg
6-w/o twg pkg
7-2WD exc PreRunner
8-4WD and PreRunner
9-Best choice for fuel economy and cold starting